Claim Amendments

- 1. (Currently Amended) A method, comprising:
- writing data fragments to a non-volatile memory; and

updating entries of a sequence table entries to a volatile memory that identify locations of the data fragments written to the non-volatile memory; and

writing the sequence table from the volatile memory to the non-volatile memory at least one of when the sequence table is full and when writing the data fragments to the non-volatile memory is completed.

- 2-4. (Canceled)
- (Currently Amended) A <u>The</u> method of claim 1, further comprising: updating a transaction indicator in the non-volatile memory prior to writing a transaction to the non-volatile memory; and

updating the transaction indicator in the non-volatile memory after writing the transaction to the non-volatile memory,

wherein the transaction comprises the data fragments and the sequence table entries.

6. (Currently Amended) A The method of claims 1, further comprising:

allocating a data fragment header associated to the data fragment in the non-volatile memory prior to writing a data fragment of the data fragment is to the non-volatile memory, wherein the data fragment header is associated to the data fragment; and

validating the data fragment header after writing the sequence table entries to the non-volatile memory.

7. (Currently Amended) A The method of claim 1, comprising:

allocating a sequence table header associated with the sequence table in the non-volatile memory prior to writing the sequence table to the non-volatile memory, wherein the sequence table header is associated with the sequence table; and validating the sequence table header after writing the sequence table entries to

validating the sequence table header after writing the sequence table entries to the non-volatile memory.

- 8. (Currently Amended) A system, comprising:
- a non-volatile memory;
- a volatile memory; and
- a processor to:

write data fragments to a non-volatile memory; and

update <u>entries of a sequence table entries</u> to a volatile memory that identify locations of the data fragments written to the non-volatile memory; <u>and</u> Docket: P21119

write the sequence table from the volatile memory to the non-volatile memory at least one of when the sequence table is full and when writing the data fragments to the non-volatile memory is completed.

9-11. (Canceled)

 (Currently Amended) A <u>The</u> system of claim 8, wherein the processor further:

updates a transaction indicator in the non-volatile memory prior to writing a transaction to the non-volatile memory; and

updates the transaction indicator in the non-volatile memory after writing the transaction to the non-volatile memory,

wherein the transaction comprises the data fragments and the sequence table entries.

 (Currently Amended) A <u>The</u> system of claims 8, wherein the processor further:

allocates a data fragment header associated to the data fragment in the non-volatile memory prior to writing a data fragment of the data fragments to the non-volatile memory, wherein the data fragment header is associated to the data fragment: and

App. No. 10/591,933

validates the data fragment header after writing the sequence table entries to the non-volatile memory.

 (Currently Amended) A <u>The</u> system of claim 8, wherein the processor further:

allocates a sequence table header associated with a sequence table in the non-volatile memory prior to writing the sequence table to the non-volatile memory,

wherein the sequence table header is associated with the sequence table; and validates the sequence table header after writing the sequence table entries to the non-volatile memory.

15. (Currently Amended) A machine-readable medium storage device comprising a plurality of instructions which when executed result in an apparatus: writing data fragments to a non-volatile memory; and updating entries of a sequence table entries to a volatile memory that identify locations of the data fragments written to the non-volatile memory; and

writing the sequence table from the volatile memory to the non-volatile memory at least one of when the sequence table is full and when writing the data fragments to the non-volatile memory is completed.

16-18, (Canceled)

19. (Currently Amended) The machine-readable medium storage device of claim 15 wherein the plurality of instructions further result in the apparatus:

updating a transaction indicator in the non-volatile memory prior to writing a transaction to the non-volatile memory; and

updating the transaction indicator in the non-volatile memory after writing the transaction to the non-volatile memory,

wherein the transaction comprises the data fragments and the sequence table

20. (Currently Amended) The machine-readable medium storage device of claim 15 wherein the plurality of instructions further result in the apparatus:

allocating a data fragment header associated to the data fragment in the non-volatile memory prior to writing a data fragment of the data fragments to the non-volatile memory, wherein the data fragment header is associated to the data fragment; and

validating the data fragment header after writing the sequence table entries to the non-volatile memory.

 (Currently Amended) The machine-readable medium storage device of claim 15 wherein the plurality of instructions further result in the apparatus: allocating a sequence table header associated with a sequence table-in the non-volatile memory prior to writing the sequence table to the non-volatile memory, wherein the sequence table header is associated with the sequence table; and validating the sequence table header after writing the sequence table entries to the non-volatile memory.